

SmartPanel Basic Features:

Feature	Acrylic Panels
Surface Finish	<ul style="list-style-type: none"> • Highest gloss level > 90% • Most consistent finish • No orange peel, no ripples
Edge finish	<ul style="list-style-type: none"> • High Quality edge finish achievable due to 1mm colour thickness • Almost seamless with EVA, PUR, Air fusion or Laser edge band
Durability	<ul style="list-style-type: none"> • Moderate durability • Easy to repair
Fabrication	<ul style="list-style-type: none"> • Easiest to fabricate • Router or saw cutting • Protective masking supplied standard
Colour & Panel Thickness	<ul style="list-style-type: none"> • 1mm thick colour faces. Laminated double- sided. Any thickness board is suitable from 3 to 50 mm
Lead-time	<ul style="list-style-type: none"> • Stock available at distribution centres for next day shipment • For doors: 10 working days from placement of order • For non-stocked colours/finishes: to be confirmed
Consistency	<ul style="list-style-type: none"> • Highest level of consistency • Stringent quality standards • Visual inspection of every panel during process
Cost	<ul style="list-style-type: none"> • Moderate cost • Double-sided and single-sided options
Market Sectors	<ul style="list-style-type: none"> • Medium to high level market sectors • Superior quality, consistency and short lead times offer major benefits
Warranty	<ul style="list-style-type: none"> • 15-year indoor warranty