

RESOPAL® TRACELESS

CLEANING AND MAINTENANCE

1. Material description and composition

RESOPAL®-Traceless is a laminate panel with an anti-fingerprint, matt, low-reflection and soft-touch surface that is designed for use in interior design. Although RESOPAL®-Traceless meets the requirements based on DIN EN 438, Part 3, it is not a high-pressure laminate in the sense of DIN EN 438 on account of the surface material used. RESOPAL®-Traceless is postformable within limits; it is therefore advisable to perform tests beforehand.

2. General cleaning

Light soiling can be cleaned easily with clear, lukewarm water. Heavier soiling can be cleaned with either soap or a detergent sud.

- No scouring agents should be used. Cleaning agents have always to be diluted with water
- Clean and fine cloths or sponges should be used
- Always use a clean cloth with clear water to rewash the sheets to avoid streak

On no account should the following cleaning agents be used

- Scouring cleaning solutions (e.g. scouring powder or -milk)
- Solvents or solvent-containing pastes (Acetone, benzine, thinners etc.)
- Scouring or abrasive cleaning cloths or sponges (e.g. microfiber cloths, scouring sponges, wire wool etc.)

All the information given in this product data sheet is based on current scientific knowledge but cannot be warranted. Suitability for specific purposes or applications cannot be guaranteed.